

IN THE CLAIMS:

1. (Currently Amended) A cutting tool, comprising:

a saw blade,

a blade case comprising a blade cover adapted to
substantially cover at least one lateral side of the saw blade and

a light disposed within the blade case, wherein the light is displaced from the saw blade in a lateral direction that is substantially perpendicular to a face of the saw blade, the light is substantially aligned with a cutting line of a workpiece that will be cut by the saw blade during a cutting operation, and

wherein the blade ~~case~~ cover includes an inner wall and the light is mounted to a part of the inner wall that opposes to the saw blade in the lateral direction.

2. (Original) A cutting tool as in claim 1, further comprising a mounting device adapted to receive the light, wherein the mounting device is disposed within the blade case.

3. (Original) A cutting tool as in claim 2, wherein the blade case comprises a side portion that laterally opposes the saw blade and the mounting device is disposed within the side portion.

4. (Previously Amended) A cutting tool as in claim 3, wherein the mounting device comprises a cover member that substantially protects the light from the saw blade, wherein a gap is maintained

to permit light to be directed to a portion of the workpiece that will be cut.

5. (Previously Amended) A cutting tool as in claim 4, wherein a direction of the light is substantially parallel to the saw blade.

6. (Original) A cutting tool as in claim 4, further comprising a power supply circuit adapted to supply power to the light, wherein the cover member defines a space for receiving the light and a portion of the power supply circuit.

7. (Original) A cutting tool as in claim 6, wherein the power supply circuit includes a socket and an electrical line extending from the socket, the socket being coupled to the mounting device, wherein the socket and a portion of the electrical line are disposed within the space of the cover member.

8. (Canceled)

9. (Canceled)

10. (Original) A cutting tool as in claim 1, wherein the cutting tool is a portable circular saw, the saw blade is a circular saw blade and the light is laterally displaced from the

circular saw blade along the rotational axis of the circular saw blade.

11. (Original) A cutting tool as in claim 10, further comprising:

a base adapted to contact the workpiece during the cutting operation and

a saw unit arranged and constructed to vertically pivot relative to the base, wherein the blade case is a portion of the saw unit and the blade case comprises at least one side portion that laterally opposes the circular saw blade and wherein the light is disposed within the side portion.

12. (Original) A cutting tool as in claim 11, further comprising a mounting device disposed within the side portion, the mounting device receiving the light.

13. (Original) A cutting tool as in claim 1, further comprising:

a base adapted to contact the workpiece during the cutting operation, wherein the blade case is adapted to vertically pivot relative to the base,

a handle coupled to the blade case and

a power supply circuit adapted to supply power to a motor and to the light, wherein elements of the power supply circuit are

arranged to horizontally balance the cutting tool when the base extends substantially in a horizontal direction and the cutting tool is held by the handle.

14. (Original) A cutting tool as in claim 13, wherein the power supply circuit comprises a transformer that is disposed substantially in a vertical plane that extends through the handle.

15. (Original) A cutting tool as in claim 14, further including a power switch and a lighting switch mounted on the handle and being positioned adjacent to each other, the power switch being operable to start the motor and the lighting switch being operable to turn on the light.

16. (Original) A cutting tool as in claim 1, wherein the cutting tool is a portable circular saw, the saw blade is a circular saw blade and the light is laterally displaced from the circular saw blade along the rotational axis of the circular saw blade, wherein the lighting direction is substantially parallel to the saw blade, the cutting tool further comprising:

a base adapted to contact the workpiece during the cutting operation,

a mounting device constructed to receive the light,

a saw unit arranged and constructed to vertically pivot relative to the base, wherein the blade case is a portion of the

saw unit, the blade case comprises a side portion that laterally opposes the circular saw blade and the light and the mounting device are disposed within the side portion,

a handle coupled to the saw unit,

a cover member disposed to substantially protect the light from the saw blade, wherein a gap is maintained to permit light to be directed to the portion of the workpiece that will be cut,

a power supply circuit adapted to supply power to a motor and to the light, wherein elements of the power supply circuit are arranged to horizontally balance the cutting tool when the base extends substantially in a horizontal direction and the cutting tool is held by the handle, wherein the power supply circuit comprises a transformer that is disposed substantially in a vertical plane that extends through the handle and a socket and an electrical line extending from the socket, the socket being coupled to the mounting device, wherein the socket and a portion of the electrical line are disposed within a space defined within the cover member,

a power switch mounted on the handle and operable to start the motor and

a lighting switch mounted on the handle and being positioned adjacent to the power switch, the lighting switch being operable to turn on the light.

17. (Original) A cutting tool as in claim 16, further including a cooling device adapted to cool the light during operation and to produce a flow of air to cool the motor, wherein at least one vent opening is formed in the blade case, cooling air is directed to flow into the blade case through the at least one vent opening and the cover member is arranged and configured to direct cooling air from the vent opening to flow across the light so as to cool the light.

18. (Currently Amended) A cutting tool comprising:

a saw blade,

a blade case comprising a blade cover adapted to substantially cover at least one lateral side of the saw blade,

a motor housing adapted to accommodate a motor for driving the saw blade, wherein the blade case and the motor housing are formed separately from each other and are adapted to be joined to each other along a joining line,

a light adapted to illuminate a portion of a workpiece that will be cut by the saw blade during a cutting operation, wherein the light is laterally displaced from the saw blade and the light is substantially aligned with a cutting line of a workpiece that will be cut by the saw blade during a cutting operation, and wherein the blade cover includes an inner wall and the light is mounted to a part of the inner wall that opposes to the saw blade in the lateral direction,

a power supply circuit adapted to supply power to the light, wherein the power supply circuit comprises a first circuit portion disposed within the motor housing and a second circuit portion disposed within the blade case and

a coupling connecting the first circuit portion and the second circuit portion.

19. (Original) A cutting tool as in claim 18, further including a mounting device disposed within the blade case and receiving the light.

20. (Previously Amended) A cutting tool as in claim 18, wherein the coupling is operable to connect the first circuit portion and the second circuit portion from an outer side of the tool after the motor housing and the blade case have been joined to each other.

21. (Previously Amended) A cutting tool as in claim 20, further comprising:

a recess formed in an outer surface of the cutting tool adjacent to the joining line that accommodates the coupling and

a coupling cover that covers the coupling from an outside when the coupling is accommodated within the recess.

22. (Original) A cutting tool as in claim 18, wherein the coupling is adapted to automatically connect the first and second circuit portions at the same time that the blade case and the motor housing are joined to each other.

23. (Canceled)

24. (Canceled)

25. (Canceled)

26. (Previously Added) A cutting tool as in claim 17, wherein the power supply circuit comprises:

a motor housing accommodating a motor for driving the saw blade, wherein the blade case and the motor housing are formed separately from each other and are joined to each other along a joining line,

a first circuit portion disposed within the motor housing and a second circuit portion disposed within the blade case, and

a coupling connecting the first circuit portion and the second circuit portion, wherein the coupling is arranged and constructed to connect the first circuit portion and the second circuit portion from the outer side of the tool after the motor housing has been joined to the blade case.

27. (Canceled)

28. (Canceled)

29. (Canceled)